

SECTION 09 84 00

1/2" ACOUSTICAL WALL TREATMENT

1/2" Low Density Exposed ReCore

PART 1 — GENERAL

1.01 SUMMARY

- A. Provide Acoustical Wall Treatment using ReCore Acoustic Substrate installed as shown on the drawings, as specified herein and as needed for a complete and proper installation.
- B. Contractor will perform a "value engineering" review of provided drawings, seeking product manufacturers input as appropriate, and make recommendations for the benefit of the project.

1.02 RELATED WORK

- A. Documents affecting work of this section include, but are not necessarily limited to, General Conditions, Supplementary Conditions, and sections in Division 1 of these Specifications.

1.03 SUBMITTALS

- A. General: Submit five (5) copies of the following in accordance with Conditions of Contract and Division 1 Specification Sections.
- B. Product Data: Submit manufacturer's technical data, installation instructions, and maintenance and cleaning instructions.
- C. Certified Test Reports: Submit test data for the manufacturer's products from an independent testing agency, acceptable to authorities having jurisdiction, evidencing the panel components and/or assemblies comply with requirements indicated for acoustical and fire performance characteristics.
- D. Provide a copy of the Manufacturer's Lifetime Warranty on ReCore certificate. All Warranty Certificates must include the Project Registration Number to ensure validity of Manufacturer's Warranty. Warranty certificates without a registration number are not valid.
- E. Samples:
 - 1. Core Material — Submit 8 ½" X 11" samples of each core material used, showing full range of materials, facings, colors, thicknesses, acoustics, and density.

PROJECT NAME
PROJECT OWNER
BID NO. _____

DATE

EXPOSED RECORE
ACOUSTICAL WALL TREATMENT
09 84 00 — 1 OF 6

1.04 QUALITY ASSURANCE

- A. Contractor: Provide verifiably genuine products for each type of wall panel as produced by the manufacturer(s), including recommended primers, adhesives, and sealants. The manufacturer's published product literature shall clearly indicate compliance of wall panels with requirements indicated.
- B. Both individual components and finished assemblies shall meet the following as appropriate:
 - 1. Thickness: 1/2", Density: 4.5 pcf.
 - 2. Fire Performance Characteristics: Provide ReCore panels with surface-burning characteristics as indicated below, as determined by testing to ASTM E-84 Class A, by a testing organization acceptable to authorize having jurisdiction.
 - i. Flame Spread: 25 or less
 - ii. Smoke Developed: 450 or less
 - 3. Sound Absorption Characteristics: Provide ReCore wall panels with a noise reduction coefficient (NRC) of 0.4 or better.
 - 4. Be free of volatile organic compounds (VOCs).
 - 5. Fungi Resistance Certification of core material in accordance with ASTM C 1338.
 - 6. Color: Bright white, consistent within each sheet and across all sheets installed in each location.

1.05 DELIVERIES, STORAGE, AND HANDLING

- A. Protect the core material from excessive moisture in shipment, storage, and handling. Deliver in unopened bundles and store in a dry place with adequate air circulation. Do not deliver material until wet work such as concrete and plaster has been completed.

1.06 PROJECT CONDITIONS

- A. Do not begin installation until spaces to receive the Acoustical Wall Treatment have been enclosed and maintained at approximately the same humidity and temperature conditions as planned for occupancy. Maintain temperature conditions as recommended by panel manufacturer.

1.07 EXTRA MATERIALS

- A. No extra free materials are to be provided.
- B. Contractor to provide Owner/District additional system materials at manufacturer's current retail price.

PART 2 — PRODUCTS

2.01 RECORE ACOUSTIC MATERIAL

- A. Available Manufacturers: Subject to compliance with requirements, the product used as basis-of-design is provided by the manufacturer listed below:
ReCore Acoustical Substrate, as distributed by Fabricmate Systems, Inc., P:(805)642-7470,
F:(805)642-3154, Toll Free:(866)622-2996, www.fabricmate.com. No substitutions accepted.

PROJECT NAME
PROJECT OWNER
BID NO. _____

DATE

EXPOSED RECORE
ACOUSTICAL WALL TREATMENT
09 84 00 — 2 OF 6

1. Contractor shall provide a Lifetime ReCore Warranty Certificate.
- B. Design Requirements:
 1. The direct-applied acoustic wall treatment must be placed in locations where it will be subjected to minimal touching, abrasion, or any other type of direct mechanical contact, during the normal use of the facility.
 2. Panels must be inspected for dimension, square, cleanliness, color and surface quality prior to installation. Panels must be stored in a clean, dust-free environment. All handling shall be done using clean cloth gloves and particular care must be taken to avoid smudges, palm prints, spills, splattering or any other type of marring of the exposed surfaces and edges
 3. ReCore panels shall be secured on a properly prepared surface using manufacturer's standard mechanical fasteners and adhesives. All adhesives must be tested for suitability for the surface of the wall where ReCore is applied.
 4. Panels which are not manufactured from ReCore, as sold by Fabricmate Systems, Inc. or those wrapped in fabric, do not satisfy the intent of this specification and will not be accepted.
 5. Fire resistance: Complete panel assembly shall have an ASTM E-84 Class A.

PART 3 — EXECUTION

3.01 INSPECTION

- A. Contractor must examine substrates and conditions under which the exposed ReCore is to be applied and notify the Architect in writing of conditions detrimental to proper and timely completion. Do not proceed with work until unsatisfactory conditions have been deemed corrected and acceptable to contractor.
- B. Verify that all stationary objects abutting acoustical treatment panels are installed (i.e. casework, marker boards, door and window jams, ceiling) prior to installation.

3.02 INSTALLATION

- A. Install exposed ReCore wall panels in locations indicated on plans. Comply with manufacturer's printed instructions for installation.
- B. Prep surfaces that receive the exposed ReCore panel treatment; remove all obstacles. Attach core to mounting surface per manufacturer's specifications. Mechanically fasten core to prevent air gaps between core and wall and to assure proper adhesion.

3.03 CLEANING AND PROTECTION

- A. Clean exposed surfaces of the exposed ReCore panels; comply with manufacturer's instructions for cleaning and repair of minor finish damage.
- B. The sub-contractor shall advise the general contractor of the required protection for the exposed ReCore panels, such as; temperature and humidity limitations and dust control, so that the finished work will be without damage and deterioration at the time of acceptance by the Owner/District.

3.04 WARRANTY

- A. All exposed ReCore acoustic panels have a Lifetime Manufacturers' Warranty against material or process manufacturing defects, commencing on the date of substantial completion. Warranty does not cover soiling or defects due to denting or abrasion.

PROJECT NAME
PROJECT OWNER
BID NO. _____

DATE

EXPOSED RECORE
ACOUSTICAL WALL TREATMENT
09 84 00 — 3 OF 6

1. All certificates of warranty must include the Manufacturer's Project Registration Number, which must be obtained by installer prior to the date of installation. Project Registration Numbers may not be obtained after the installation has commenced.
2. Warranty Certificates without a Manufacturer's Project Registration Number shall be deemed as invalid and unenforceable.

3.05 SECURITY

- A. Contractor shall meet all requirements, as described by California Education Code §45125.1.

END OF SECTION 09 84 14

PROJECT NAME
PROJECT OWNER
BID NO. _____

DATE

EXPOSED RECORE
ACOUSTICAL WALL TREATMENT
09 84 00 — 4 OF 6