FS155 - 1" SQUARE FRONT-LOAD LOW-LEG







Aesthetics, Acoustics, and Wall Protection in Hallway


FS155 is a Low-Leg Frame used as a perimeter piece for 1" where limited Frame visibility is desired. The Frame jaws are recessed, resulting in less visibility. Frame will still be slightly visible in most cases and we do offer custom colors, textures, and styles. Combined with our ReCore®


Backing and Fabric, this Frame can be used to create anything from full-wall photographic murals to smaller acoustic or bulletin-board panels as well as Wainscoting and other types of Wall Protection. Use our Flex-Frame for creating curved designs or installing on rounded surfaces.


FS155 FRAME FEATURES














100% uPVC | CRUSH PROOF | FULLY RECYCLABLE | FLEXIBLE | EASILY CUSTOMIZABLE | SAFE TO HANDLE








Acoustics, Aesthetics, and Wall Protection in Home Theater

Our "Natural" color Frame is a great option when you want a low-key perimeter around your panel or installation. If you're looking for something that stands out a bit more, we will soon be offering a number of color and style options (examples below) that are sure to take your panel or full-wall installation to the next level.

ACOUSTICS











FS155 Profile (Actual Size) Black White **Brushed Aluminum** Wood Grain

FS155 FRAME FEATURES		FEATURE DESCRIPTION
Height	1"	One-Inch Frame is ideal for acoustic applications, offering excellent sound absorbency, tackability, and wall protection
Edge Profile	Square	The square profile produces clean, crisp joints and edges
Load	Front-Load	FS155's front loading feature allows it to be placed up against almost any surface including walls, door moldings, etc
Seam Usage	No	FS155 cannot be used to create seams or joints
Edge Usage	Yes	FS155 can be used as a perimeter with any 1" substrate
Other	Curvable	We offer our curvable Flex-Frame (SKU: KF155) or FS155 can be easily modified on-site to create curved joints

FS155 TECHNICAL CUTAWAY

FRAME **FABRIC** STAPLE BACKING/SUBSTRATE **FULL HEIGHT** FROM WALL 1.121"-1.24" 2 **HEIGHT** ALLOWANCE FOR SUBSTRATES AIR GAP (APPROX) 0.102"

FS155 SPECIFICATIONS

Description Durable uPVC Track for use in Fabric Wall Finishing

Sold In 5' Lengths

Installation Mountable with

• 18 Gauge 1/4" Full-Crown Staples

Drywall Screws

Staples & Adhesive (Liquid Nails or PL200 Recommended)

Customization Easily cut with:

Fabricmate[®] Chamfer Cutters

180 Tooth 10" Plastic Weight Chop Saw

Composition

100% Durable uPVC (No Phthalates or BPA, Does not decompose, is weather-resistant)

5' x 1.175" x 0.625" **Dimensions**

> Weight 1.2 lb per 5' stick

Disposal Fully Recyclable

Handling Safe To Handle

Fire Rating ASTM E84 Class A

> VOC's < 0.1%



2781 Golf Course Drive, Unit A Ventura, CA 93003 805-642-7470 fabricmate.com