FS150 HF Track

Data Sheet





FS150 HF can be used as a perimeter, intermediate piece and as an inside corner piece for 1" square profile installations.

FS150 HF is built with more channel space to accommodate heavier fabrics. Available in a range of colors. Pantone Match Color Available. (Lead times & minimum quantities apply) This Track is perfect for use with our Fabric Wall Finishing System. Combined with our ReCore[®] Backing and Fabric, this track can be used to create anything from full-wall photographic murals to smaller acoustic or bulletin-board panels as well as Wainscoting and other types of Wall-Protection.





FS150HF EDGE & JOIN I ON SAMPLE PAR FS150HF-NAT (NATURAL) SHOWN

TRACK FEATURES

Height	Edge Profile	Load Direction	Seam Usage	Edge Usage	Other
		L		++++ ++++	HF
1" THICK	SQUARE	FRONT	YES	YES	HEAVY FABRIC

FS150 HF Track

Data Sheet

Color	White	Natural	Dark Brown	Black
Part #	FS150HF-WHT	FS150HF-NAT	FS150HF-DKB	FS150HF-BLK
η				

Track Features		Feature Description
Height	1"	One-Inch Track is ideal for acoustic applications, offering excellent sound absorbency, tackability and wall-protection.
Edge Profile	Square	The square profile produces clean, crisp joints and edges.
Load	Front-Loading	Front loading track can be placed up against almost any surface including walls, door moldings, etc.
Usage	Edge & Joint	Can be used as both a perimeter and intermediate (mid-wall) track with any 1 inch substrate.
Other	Heavy Fabric	Built with more channel space to accommodate heavier fabrics

TECHNICAL CUTAWAY



FS150 SPECIFICATIONS

Description	Durable PVC Track for use in Fabric Wall Finishing		
Sold In	5' Lengths		
Installation	Mountable with • Drywall Screws • 18 Gauge 1/4" Full-Crown Staples • Adhesive		
Customization	Easily cut with: • 180 Tooth 10" Plastic Weight Chop Saw		
Composition	100 % Durable PVC		
Dimensions	5' x 1" x .625"		
Weight	1 lb per 5' stick		
Disposal	Fully Recyclable		
Handling	Safe To Handle		
Fire Rating	ASTM E84 Class A		
VOC's	< 0.1%		

